

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	25
Ratio (i=)		56
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	1.1
Service factor		1.1
Rated Power P1	[kW]	1.17

Output data

Gear unit **M RS 85 PC 56 90 B14 AC 32 MT 1.1 kW 90 S4 B14 X3 B3**

Type		RS - Worm speed reducers
Input type		M
Size		85
Ratio (i=)		56
Input flange		B14
Mounting position		B3
Input speed	[rpm]	1400
Output speed	[rpm]	25
Rated output torque	[Nm]	285.74
Service Factor		1.1
Efficiency		0.68
Inertia moment	[kgm ²]	0.000341

Gear unit configuration

Output shaft	Hollow output shaft
Fixing	Shaft mounting
Version	PC

Output radial and axial loads

Ball bearings output radial load	[N]	6600
Taper bearings output radial load	[N]	8700
Ball bearings output axial load	[N]	1320
Taper bearings output axial load	[N]	1740

Accessories


Hollow output shaft	AC 32
---------------------	-------

Electric motor

Size		90 S4
Poles		4
Power	[kW]	1.1


Electric motor configuration

Motor flange	B14
Terminal box position	X3




M RS 85 PC 56 90 B14 AC 32 MT 1.1 kW 90 S4 B14 X3 B3

Mounting positions



Terminal box position




0.6



← Oil quantity [litres]

Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	13.5
Electric motor [kg]	12

Gearing data

Axial module	2.5
Number of starts	1
Lead angle	4° 45'
Pressure angle	20°

Backdriving

Static self-locking
Slow back-driving in case of vibrations
Low dynamic back-driving