

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	65.03
Ratio (i=)		21.53
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	0.37
Service factor		1
Rated Power P1	[kW]	0.36

Output data

Gear unit	M RD 02 B3 H1 21.53 71 B14 AU 20x40 MT 0.37 kW 71 B4 B14 X3
------------------	--

Type		RD - Helical gearboxes
Input type		M
Size		02
Ratio (i=)		21.53
Input flange		B14
Mounting position		H1
Input speed	[rpm]	1400
Output speed	[rpm]	65.03
Rated output torque	[Nm]	52.17
Service Factor		1
Efficiency		0.96
Inertia moment	[kgm ²]	0.000031

Gear unit configuration

Fixing		Feet
Output shaft		AU 20x40

Output radial and axial loads


Output radial load	[N]	1170
Output axial load	[N]	234

Electric motor

Size		71 B4
Poles		4
Power	[kW]	0.37


Electric motor configuration

Motor flange		B14
Terminal box position		X3




M RD 02 B3 H1 21.53 71 B14 AU 20x40 MT 0.37 kW 71 B4 B14 X3

Mounting positions



Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	3
Electric motor [kg]	6.2

M RD 02 B3 H1 21.53 71 B14 AU 20x40 MT 0.37 kW 71 B4 B14 X3