

Input data

System of measurement		Metric
Input type		Gear motor
Input speed	[rpm]	1400
Output speed	[rpm]	538.46
Ratio (i=)		2.6
Frequency	[Hz]	50
Input options		IEC
Requested input power	[kW]	22
Service factor		3.5
Rated Power P1	[kW]	76.32

Output data

Gear unit M RD 62 B3 H1 2.6 180 B5 AU 50x100 MT 22 kW 180 L4 B5 X3

Type		RD - Helical gearboxes
Input type		M
Size		62
Ratio (i=)		2.6
Input flange		B5
Mounting position		H1
Input speed	[rpm]	1400
Output speed	[rpm]	538.46
Rated output torque	[Nm]	374.58
Service Factor		3.5
Efficiency		0.96
Inertia moment	[kgm ²]	0.006719

Gear unit configuration

Fixing		Feet
Output shaft		AU 50x100

Output radial and axial loads


Output radial load	[N]	5100
Output axial load	[N]	1020

Electric motor

Size		180 L4
Poles		4
Power	[kW]	22


Electric motor configuration

Motor flange		B5
Terminal box position		X3




M RD 62 B3 H1 2.6 180 B5 AU 50x100 MT 22 kW 180 L4 B5 X3

Mounting positions



Lubricant type: Long life synthetic oil ISO VG320

Direction of rotation



Weight

Gear unit [kg]	62
Electric motor [kg]	135

M RD 62 B3 H1 2.6 180 B5 AU 50x100 MT 22 kW 180 L4 B5 X3